



26-INCH LCD MONITOR

- 1366 x 768 Resolution
- Bright 500 cd/m² Display
- HDMI, VGA Inputs
- 3D Comb Filter with De-Interlace
- 2x Looped BNC Inputs
- VESA Compliant Hole Pattern
- Unit accepts 3-prong 110 VAC Cable at the Monitor. No external power adapter required.

S P E C I F I C A T I O N S

26-inch CCTV LCD Monitor		Part Number - SM26M-B
Display	Screen Size	26"
	Aspect Ratio	16:9
	Resolution	1366 x 768
	Brightness (cd/m ²)	500
	Response Time	8 ms
	Viewing Angle (H/V)	170° / 170°
	Contrast Ratio	1000:1
	Pixel Pitch	0.1405 x 0.4215mm
Video Inputs	Digital Inputs	HDMI, VGA
	Composite Inputs / Outputs (BNC)	2 / 2
Audio	Audio Input	1/8" Phono Jack
	Audio Output(s)	2 x RCA Out (L/R)
Power	Power Consumption	< 130W
Design Features	Features - Signal Filter	3D-Comb, De-Interlace
	Features - PIP - I composite, I digital	Yes
	Wall Mount Hole Pattern	200 x 100mm
	Remote	Included
	Power Supply	N/A, unit accepts 110VAC
	Connector Location / Secured	Side / Yes
Standards	Approvals	CE, FCC, RoHS
Dimensions	Dimensions w/o stand (H/W/D)	25.2 x 15 x 3.55 in (640.8 x 381 x 90.2 mm)
Weight	Monitor Weight	25.4 lbs (11.5kg)