



Go!Bridge IP Communicator

SKU: 2GIG-BRDG1-900

UPC: 8-17082-01050-2

We are pleased to announce the availability of the Go!Bridge™ IP Communicator (2GIG-BRDG1-900). The IP Communicator provides Internet connectivity between the Go!Control® Panel and the monitoring service's Central Station. To enable connectivity, the 900 MHz Transceiver (2GIG-XCVR2-345) must be installed in the Control Panel.

It supports firmware updates over the Internet, provides interactive security services, and enables supervision using signal-forwarding to the Central Station. For wireless communication with the Control Panel, the 900MHz Transceiver Module (2GIG-XCVR2-345) must be installed in the panel. The Go!Bridge also connects to the Internet via a local network router using an Ethernet cable (not provided).

FEATURES

- Secure Internet reporting capabilities
- 256-bit AES Encryption
- Wireless panel integration via 900MHz frequency
- CAT5 Ethernet quick connection to hub/router
- Full Contact ID with high-speed reporting
- Remote access capabilities via Internet or smartphone
- Easy install behind firewalls
- DHCP Addressing for IP network
- Free firmware update option over the Internet

SPECIFICATIONS

- **Wireless Signal Range:** 500 ft, open air, with Wireless Control Panel
- **Transceiver:** Silicon Labs SI1001-E-GM2
- **Transceiver Frequency:** 25 channel frequency-hopping spread spectrum, 403 kHz channel spacing (910.2-920.275 MHz)
- **Modulation Type:** GFSK modulation, 128 kpbs
- **RF Power:** +19dBm Maximum
- **Ethernet:** 10/100 BaseT
- **Dimensions (L x W x H):** 6.24 x 4.5 x 1 in
- **Weight:** 9.6 oz
- **Housing Material:** Cycloy™ Resin C2800 (Rated to UL 94 V-0: Flammability Standard)
- **Color:** White
- **Operating Temperature:** 32° F to 120.2° F, (0° C to +49° C)
- **Relative Humidity:** 5-95% Non-Condensing
- **Operating Voltage:** 5VDC
- **Certification:** ETL, FCC, IC, IFETEL, and NOM

PRICING

Contact your 2GIG Distributor or Sales Representative for pricing details.

PRODUCT AVAILABILITY, ORDERING, AND SHIPPING INFORMATION

Orders for the new SKU will be accepted starting on December 1, 2014. The estimated first order date from distributors is December 8, 2014. Dealers should check with distributors for availability.

SYSTEM REQUIREMENTS

- Go!Control Panel
- Firmware version 1.12 or higher
- 2GIG-XCVR-345 900 MHz Transceiver
- Internet connection

WARRANTY

The new SKU ships with a standard one (1) year limited warranty. Refer to the Installation Instructions for specific warranty details.