


**SPECIFICATIONS**

MODEL : AUD    HP: \_\_\_\_\_

VOLTS : \_\_\_\_\_ PHASE : \_\_\_\_\_

- \* UL AND CANADIAN UL LISTED
- \* HIGH STARTING TORQUE, CONTINUOUS DUTY MOTOR
- \* MOTOR OVERLOAD PROTECTION
- \* ELECTRO-MECHANICAL MODELS
  - \* CLASS 2 (24 VOLT) CONTROL CIRCUIT
  - \* IEC REVERSING CONTACTOR RATED 1-1/2 HP
- \* SOLID STATE CONTROL MODELS (SUFFIX "S")
  - \* CLASS 2 (24 VOLT) CONTROL CIRCUIT WITH ADVANCED SWITCH SELECTABLE FEATURES
  - \* HIGH AMP, INDUCTIVE LOAD RATED RELAYS

- \* SOLENOID BRAKE (OPTIONAL ON 1/3 & 1/2 HP)
- \* THREE BUTTON CONTROL: OPEN, CLOSE, STOP
- \* WIRED TO ACCEPT REVERSING EDGE INPUT
- \* HEAVY GAUGE, POWDER-COATED STEEL FRAME RAILS AND CONTROL BOX
- \* ALL SPROCKETS AND PULLEYS PINNED OR KEYED, SOLID STEEL DRIVE SHAFTS
- \* FULLY ADJUSTABLE FRICTION CLUTCH
- \* MANUAL DOOR DISCONNECT
- \* FULLY ADJUSTABLE, INTERNAL, SHAFT DRIVEN LIMITS

TOLERANCE (EXCEPT AS NOTED) DECIMAL X.X ±0.030 X.XX ±0.020 X.XXX ±0.010	 c.p. ALLSTAR CORPORATION PO Box 240 Downingtown, PA 19335		APPROVED BY	SCALE	DRAWN BY
				N/A	CPC
FRACTIONAL ±1/32	MATERIAL		DATE	08-26-96	
ANGULAR ±1°	N/A		SHT	1 OF 1	
TITLE	DWG NO.	REV			
DWG, DIMENSIONS/SPECIFICATIONS, MODEL AUD	107093	C	© 1998		