


## SPECIFICATIONS

MODEL : J      HP: \_\_\_\_\_

VOLTS : \_\_\_\_\_ PHASE : \_\_\_\_\_

- \* UL AND CANADIAN UL LISTED
- \* HIGH STARTING TORQUE, CONTINUOUS DUTY MOTOR
- \* MOTOR OVERLOAD PROTECTION
- \* ELECTRO-MECHANICAL MODELS
  - \* CLASS 2 (24 VOLT) CONTROL CIRCUIT
  - \* IEC REVERSING CONTACTOR RATED 1-1/2 HP
- \* SOLID STATE CONTROL MODELS (SUFFIX "S")
  - \* CLASS 2 (24 VOLT) CONTROL CIRCUIT WITH ADVANCED SWITCH SELECTABLE FEATURES
  - \* HIGH AMP, INDUCTIVE LOAD RATED RELAYS
  - \* SOLENOID BRAKE

- \* THREE BUTTON CONTROL: OPEN, CLOSE, STOP
- \* WIRED TO ACCEPT REVERSING EDGE INPUT
- \* HEAVY GAUGE, POWDER-COATED STEEL FRAME RAILS AND CONTROL BOX
- \* ALL SPROCKETS AND PULLEYS PINNED OR KEYED, SOLID STEEL DRIVE SHAFTS
- \* FULLY ADJUSTABLE FRICTION CLUTCH
- \* HEAVY DUTY PILLOW BLOCK BEARINGS ON OUTPUT SHAFT
- \* FLOOR LEVEL DISCONNECT FOR MANUAL OPERATION
- \* FULLY ADJUSTABLE, INTERNAL, SHAFT DRIVEN LIMITS

TOLERANCE (EXCEPT AS NOTED) DECIMAL X.X ± N/A X.XX ± N/A X.XXX ± N/A	 c.p. ALLSTAR CORPORATION PO Box 240 Downingtown, PA 19335		APPROVED BY	SCALE NONE	DRAWN BY CPC
			FRACTIONAL ±1/32	MATERIAL	DATE 1/09/98
ANGULAR ±1°	TITLE DWG, DIMENSIONS/SPECIFICATIONS, MODEL J		SHT 1 OF 1	© 1998	
			DWG NO. 108203	REV B	