

- Side-Opening for Quick Access
- Glass Viewing Window
- 12VDC/24VAC Dual Voltage
- Heater/Blower Included
- IP65 or IP68 Option
- Adjustable Camera Sled



Outdoor Camera Housing

The HS91 Series of outdoor-rated camera housing are outdoor-rated to protect sensitive CCTV equipment. The IP65 version includes vent holes in the rear of the housing and includes a sunshield. The IP68 version is water-tight and does not accept a sunshield. Both versions include a heater and blower that can be field-configured to operate on 12VDC or 24VAC depending on the site voltage. Liquid tight cordgrips are included in the hardware kit.

Specifications

| Part Number | HS91-2HB | HS91-2HB68 |
|------------------------------|--|--------------------|
| Environment | Outdoor | |
| IP Rating | IP65 | IP68 |
| Sunshield Included | Yes | No |
| Adjustable Mount Inc'l | Yes (2-axis) | |
| Pan Adjustment (Manual) | 360° | |
| Tilt Adjustment (Manual) | 60° (Horiz. to 60° Below Horiz.) | |
| Heater/Blower Included | Yes (Field Configure) | |
| Heater Activation | 59°F/15°C (Off at 77°F/25°C) | |
| Blower Activation | 95°F/35°C (Off at 77°F/25°C) | |
| Max Camera/Lens Size (WxHxL) | 4.5" x 2.5" x 9.5" 114 x 63 x 241mm | |
| Cable Diameter | 0.20~0.35" (5~9mm) | |
| Construction | Aluminum | |
| Viewing Window Mat'l | Glass | |
| Finish | White powder coat | |
| Input Voltage | 12VDC or 24VAC | |
| Power Requirements | Heater 0.75A (1.0A Inrush), Fan 0.2A | |
| Overall Dimen. (HxWxL) | 5.6" x 6.7" x 17" | 5.25" x 6.7" x 16" |
| Overall Dimen. (HxWxL) | 142 x 170 x 432mm | 133 x 170 x 406mm |

Internal View

